



Digital Multimeter DM352

FEATURES

- Heavy duty Shock, Dust and Drop proof.
- Fully protected on all Voltage, Current and Resistance ranges against accidental overload voltages upto 415 V AC.
- Unique basic accuracy of 0.25% on DC Voltage.
- Optional 40 KV AC/DC high voltage probe.



GENERAL SPECIFICATIONS

- Display : 3½ Digit, 0.5" LCD with LOBAT & polarity Indication.
- Power : Single standard 9V battery (Type 6F22 / 216 or equivalent).
- Over-Range Indication : '1' display with other digits blanked.
- Transient Protection : 2KV (DCV, ACV & ranges).
- Temperature co-efficient : (0.10 x Specified Accuracy) / Deg.C.
- Dimensions : Approx 100mm (W) x 180mm (H) x 54mm (D).
- Net Weight : Approx. 0.5 Kg.

ELECTRICAL SPECIFICATIONS :

At 25° C ±3° and 50% RH±10%

AC CURRENT

Range	Accuracy ±(%RDG+ counts)	Resolution
	50Hz - 500Hz	
200 µA	1.00% + 5	0.1µA
2000 µA	1.00% + 5	1µA
20 mA	1.00% + 5	10µA
200 mA	1.00% + 5	100µA
2 A	1.25% + 5	1mA
10 A	1.50% + 5	10mA

Overload Protection : 2A, 250V (Fuse Protected)

DC CURRENT

Range	Accuracy ±(%RDG+ counts)	Resolution
200 µA	0.75%+2	0.1µA
2000 µA	0.75%+2	1µA
20 mA	0.75%+2	10µA
200 mA	0.75%+2	100µA
2 A	1.00%+2	1mA
10 A	1.25%+2	10mA

Overload Protection : 2A, 250V (Fuse Protected)

AC VOLTAGE

Range	Accuracy ±(%RDG +Counts)	Resolution	Overload Protection
200mV	0.5%+5	0.1mV	±400V DC, 450V AC(40Hz-500Hz)
2000mV	0.5%+5	1mV	±1000V DC, 1000V AC (40Hz-500Hz)
20V	0.5%+5	10mV	±1000V DC, 1000V AC (40Hz-500Hz)
200V	0.5%+5	100mV	±1000V DC, 1000V AC (40Hz-500Hz)
1000V	0.5%+5	1V	±1000V DC, 1000V AC (40Hz-500Hz)

Input Impedance : 10 M shunted by less than 50pF (approx.)

RESISTANCE

Range	Accuracy ±(%RDG+Counts)	Max Voltage	Resolution
200	0.50% +3	400mV	0.1
2 K	0.50% +3	2.2 V	1
20 K	0.50% +3	2.2 V	10
200 K	0.50% +3	2.2V	100
2 M	0.50% +3	2.2V	0.001 M
20 M	0.50% +3	2.2V	0.01 M

Overload Protection : 415V AC, Open Circuit Voltage less than 3.2V

DC VOLTAGE

Range	Accuracy ±(%RDG +Counts)	Resolution	Overload Protection
200mV	0.25%+1	0.1mV	±630V DC/350AC
2000mV	0.25%+1	1mV	±1000V DC/AC
20V	0.25%+1	10mV	±1000V DC/AC
200V	0.25%+1	100mV	±1000V DC/AC
1000V	0.25%+1	1V	±1000V DC/AC

Input Impedance : 10 M (approx.)

CONTINUITY TEST

Range	Audible Threshold (Continuous Tone)	Overload Protection
🔊	≤ 10	450V AC/DC

ACCESSORIES SUPPLIED :

Pair of test leads, Instruction Manual & 9V Battery.

DIODE TEST

Built in 2 K range

we have a solution....

Rev. 08/09/00

NOTES 1.The Instrument is accompanied with Test & calibration sheet. 2.Test Facilities can be provided at the factory with the available test set-ups only. 3.The Company's policy is continuous improvement of its products. we therefore reserve the Right of any deviation from illustration or specifications without notice. 4.Stated accuracies are valid from 1/10th of range to FS. 5.Accuracy Specified for temperature range of 25°C ± 5°C & 55%RH ± 10%.



The Motwane Manufacturing Company Pvt. Ltd.



REGD. OFFICE & FACTORY : Gyan Baug, Nashik Road, Nashik - 422 101. Tel.: 91 - 253 - 2463752 / 53. Fax : 91 - 253 - 2463197 e-mail: sales@motwane.com

MUMBAI : 434 A, Gyan Ghar, 14th Road, Khar (W) Mumbai- 400 052. Tel.: 91 - 22 - 26058895 / 96 / 97 Fax : 91 - 22 -26058898 e-mail : mumbai@motwane.com

DELHI : 2 D, 2nd Floor, Vandana Building, 11, Tolstoy Marg, Cannaught Place, New Delhi-110 001.

Tel.: 011 - 41522 105. Telefax : 011 - 41522106. e-mail : delhi@motwane.com

BANGALORE : # 8/12, 3rd Floor, Honnam Complex, South Cross Road, Basavanagudi, Bangalore-560004.

Tel. : 080 - 26621186 / 26611323

For an online quotation please visit

www.motwane.com and click

'GET A QUOTE'.

